

# Portable LED Scoreboard

## with Dolphin Scoreboard Adapter



The Portable LED Scoreboard from Colorado Time Systems provides the best of both worlds: it provides the same information as two lines from the LED-R Scoreboard at a quarter of the size. The scoreboard, with its smaller size and capacity for portable use, is the affordable solution for clubs and smaller facilities. Facilities can also use the Portable Scoreboard as an auxiliary scoreboard. When connected to the Dolphin Scoreboard Adapter, data from the Dolphin system can be directly transmitted to and displayed on the Portable Scoreboard.

### Features:

- Lightweight and portable
- Includes legs and handle for easy portability
- Tripod mountable
- Optional battery operation
- Can be stacked to create multi-line auxiliary scoreboard, or entry-level scoreboard solution
- Visible from over 50 meters away
- Displays data from the Dolphin system through the Dolphin Scoreboard Adapter

### Display:

The Portable LED Scoreboard contains two lines of digits in two possible configurations:

- Two lines with ten digits each, capable of displaying one- or two-digit lane and place, in addition to time
- Top line with 6 digits to display Event/Heat and bottom line with 10 digits for lane, place, and time

1551 East 11th Street, Loveland, CO 80537 USA • phone: (970) 667-1000 • fax: (970) 667-5876



# Specifications

<b>Dimensions</b>	Height: 13.75" (34.9 cm) Width: 48" (121.9 cm) Depth: 4" (10.2 cm)
<b>Viewing Distance</b>	Over 50 meters
<b>Digit Size</b>	5" (12.7 cm)
<b>Data Connection</b>	Wireless transmission from Dolphin base to Dolphin Scoreboard Adapter, which is connected to the scoreboard
<b>Data Source</b>	Dolphin software

When not used with Dolphin, the Portable LED Scoreboard is capable of displaying all CTS scoreboard data from a System 6, 5 or 4000, including swimming, diving, water polo, synchronized swimming, and training pace clock. It incorporates all the information shown by 2 LED-R scoreboards into a smaller display.

Revised 08/07