

Colorado Time Systems - Maintenance Checklist

Product	Maintenance	Before Each Use	After Each Use	Monthly	Start of Season or when needed	End of Season (Extended Storage more than 3 months)
Start Syste	ems					_
	Check Microphone audio levels, start signal, strobe and speaker output	~			~	✓
	Check connector prongs and receptacles for corrosion and clean or replace connectors as necessary.	~			~	✓
	Flush all cable connectors that were in contact with pool water with FRESH water and let dry		~			
	Infinity and Champ: Connect charger and charge batteries for 12-24 hours (switch power OFF)		~		~	
	Pro and Elite: Charge for 4-6 hours		~		~	
	Clean all connectors using 90+% Isopropyl alcohol and a cotton swab. Protect connectors with Strikehold spray.			>	✓	✓
	Follow charging procedure according to product manual					✓
Cable Harr	nesses	•		•		
	Check connector prongs and receptacles for corrosion and clean or replace connectors as necessary.	✓			✓	✓
	Protect connectors with Strikehold spray	~		~	~	✓
	Test cable for proper operation	✓			~	
	Flush all lane connectors (Prime / A / B / C / Start / Backup Start) with clean FRESH water (not pool water)		~			
	Clean all connectors using 90+% Isopropyl alcohol and a cotton pipe cleaner.			~	~	✓
	Inspect 50pin connector hoods, replace if cracked.			~	~	✓
Wall Plate	s ·	l	l .			I
	Check connector prongs and receptacles for corrosion and clean or replace connectors as necessary.	✓		~	✓	✓
	Test wall plate for proper operation.	~		~	~	
	Clean all connectors using 90+% Isopropyl alcohol and a soft nylon brush (toothbrush) or cotton swab. Protect connectors with Strikehold spray - EXCLUDING THE FIBER CONNECTION!			~	~	✓
Deck Plate	es s					
Titanium [Deck Plates					
	Check connectors for debris and carefully remove if present.	✓			✓	
	Protect connectors with Strikehold spray.			~	✓	✓
Deck Plate	es and Quick Connect Underblock Connectors	•		•		
	Check connector prongs and receptacles for corrosion and clean or replace connectors as necessary.	✓			✓	✓
	Test Deckplate for proper operation.	~			✓	
	Flush all connectors with clean FRESH water (not pool water) and lubricate connectors with Dow #111 or equivalent		_			
	dielectric grease.		•			
	Clean all connectors using 90+% Isopropyl alcohol and a cotton pipe cleaner and lubricate connectors with Dow #111 or equivalent dielectric grease.			~	✓	✓
Quick Con	nect Deck Plates			!		
	The deck plate should be covered with or connected to one of the following at all times: * Blue deck plate plug * Cable to connection hub under the starting block * Terminator plug	~	~	~	~	~
	Check connector prongs and receptacles for corrosion and clean or replace connectors as necessary.	~			~	✓
	Flush all connectors with clean FRESH water (not pool water) and lubricate with Dow #111 or equivalent.		~			
	Lubricate connectors with Dow #111 or equivalent dielectric grease			~	✓	✓

1 of 2



Colorado Time Systems - Maintenance Checklist

Product	Maintenance	Before Each Use	After Each Use	Monthly	Start of Season or when needed	End of Season (Extende Storage more than 3 months)
Relay Judg	ing Platform - RJP			•		
	Check connector prongs and receptacles for corrosion and clean or replace connectors as necessary.	✓			~	~
	Inspect grip surface for wear or damage	~	~		✓	✓
	Test for proper operation	✓				✓
	Clean connectors using 90+% Isopropyl alcohol and a cotton pipe cleaner. Protect connectors with Strikehold spray.			~	✓	✓
ouchpad						
	Check connector prongs for corrosion and clean or replace connectors as necessary.	✓			✓	✓
	If equipped with Aquagrip, inspect for peeling	✓			✓	~
	Check for proper switch operation	✓			✓	
	Flush all connectors with clean FRESH water (not pool water)		~			
	Clean all connectors using 90+% Isopropyl alcohol and a cotton swab. Protect connectors with Strikehold spray.			~	~	✓
Timers an	d controllers (System 6, Gen7, WTTC)			1		
	Inspect the cable connectors on the back panel.	✓			✓	~
	Clean all connectors using 90+% Isopropyl alcohol and a cotton swab (see manual for details). Protect connectors with				V	J
	Strikehold spray.	_			•	•
	Update timer firmware and software. https://www.coloradotime.com/sware.htm			~	~	→
	Clean device and if applicable inserts according to manual instructions				✓	✓
Cables		1	1		ı	
	Ensure all connectors mate snugly. Connector prongs that are broken fit loosely; replace if needed.	✓		~	~	~
	Flush all connectors that were in contact with pool water with clean FRESH water		~			
	Clean all connectors using 90+% Isopropyl alcohol and a cotton swab (see manual for details). Protect connectors with			~	✓	✓
	Strikehold spray. Protect connectors with Strikehold spray				✓	~
Scoreboar					•	<u> </u>
	Verify operation of all scoreboard digits by using the test mode on the timer.	✓	1		~	~
	For units with batteries: connect charger and charge batteries for 12-24 hours w/power switch off	*	V		<u> </u>	
	Inspect the scoreboard data cable connectors for corrosion and broken or frayed wires.		<u> </u>			<u> </u>
	Clean all connectors using 90+% Isopropyl alcohol and a cotton swab. Protect connectors with Strikehold spray.					<u> </u>
LED Matri					•	<u> </u>
	Verify video operation of display by using a stored animation from the DisplayLink Plus Library	✓			✓	~
	Verify data operations by using a Swimming template and simulating a swim event on the timer.	· ·			<u> </u>	<u> </u>
	Update Displaylink Software. https://www.coloradotime.com/sware.htm	•			<u> </u>	<u> </u>
	Inspect the scoreboard data cable connectors for corrosion and broken or frayed wires.			_	<u> </u>	<u> </u>
	Inspect the scoreboard data cable connectors for signs of damage; replace if needed.				<u> </u>	<u> </u>
	Cleaning and maintenance according to manual (air filters, voltage diagnostics, communication,)				<u> </u>	<u> </u>
					Y	*
Dudius I i	If there is a DisplayLink desktop PC, have your IT department clean it inside					V
Printer	T					
	Inspect the printer cable connectors for corrosion and broken or bent pins, clean and replace as needed	✓			✓	✓